

| TEST REPORT IEC 62471:2006 Photobiological safety of lamps and lamp systems | |
|---|--|
| Report reference No | RSZ190808552-SF |
| Compiled by (+ signature) | Engineer: Taylor Chen <i>Taylor Chen</i> |
| Approved by (+ signature) | Project Engineer: Harrison Huang <i>Harrison Huang</i> |
| Date of issue | 2019-08-15 |
| Testing laboratory | Bay Area Compliance Laboratories Corp. (Dongguan) |
| Address | No.69, Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China |
| Testing location | Same as above |
| Applicant | Hongli Zhihui Group Co.,Ltd. Guangzhou Branch |
| Address | Room 316, Building 2, No.1, Xianke Yi Road, Huadong Town, Huadu District, Guangzhou, China |
| Standard | IEC 62471:2006 |
| Test sample(s) received..... | 2019-08-09 |
| Test in period..... | 2019-08-14 |
| Procedure deviation | N.A. |
| Non-standard test method | N.A. |
| <p>Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).</p> | |
| Type of test object | LED package |
| Trademark | NA |
| Model/type reference | HL-A-2835S52FC-S1-08HL |
| Manufacturer..... | Hongli Zhihui Group Co.,Ltd. Guangzhou Branch Room 316, Building 2, No.1, Xianke Yi Road, Huadong Town, Huadu District, Guangzhou, China |
| Rating | Input:3Vdc,30mA |
| <p>Copy of marking plate: None</p> | |



Test item particulars

Tested lamp: LED package
Tested lamp system: N.A

Lamp classification group.....: Exempt Group
Lamp cap: N.A
Bulb.....: N.A
Rated of the lamp: See rating
umen.

F E M N A L

| IEC 62471 | | | |
|-----------|--|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 4 | EXPOSURE LIMITS | | P |
| | Contents of the whole Clause 4 of IEC 62471: 2006 moved into a new informative Annex ZB | | P |
| | Clause 4 replaced by the following: | | P |
| | Limits of the Artificial Optical Radiation have been applied instead of those fixed in IEC 62471: 2006 | See Table 6.1 | P |
| Annex ZB | EXPOSURE LIMITS | | P |
| 4.1 | General | | P |
| | The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure | | P |
| | Detailed spectral data of a light source are generally required only if the luminance of the source exceeds $10^4 \text{ cd}\cdot\text{m}^{-2}$ | $>10^4 \text{ cd}\cdot\text{m}^{-2}$ | P |
| 4.3 | Hazard exposure limits | | P |
| 4.3.1 | Actinic UV hazard exposure limit for the skin and eye | | P |
| | The exposure limit for effective radiant exposure is $30 \text{ J}\cdot\text{m}^{-2}$ within any 8-hour period | | P |
| | To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broadband source, the effective integrated spectral irradiance, E_s , of the light source shall not exceed the levels defined by: | $E_s=1.250\times 10^{-4} \text{ W}\cdot\text{m}^{-2}$ | P |
| | $s \cdot \int_{200}^{400} \lambda \cdot \dots \cdot 30 \text{ J}\cdot\text{m}^{-2}$ | | P |
| | The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by: | | P |
| | $t_{\max}=30/E_s$ | $t_{\max}=30/(1.250\times 10^{-4})=2.40\times 10^5 \text{ s}$ | P |
| 4.3.2 | Near-UV hazard exposure limit for eye | | P |
| | For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed $10000 \text{ J}\cdot\text{m}^{-2}$ for exposure times less than 1000s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, E_{UVA} , shall not exceed $10 \text{ W}\cdot\text{m}^{-2}$ | See Table 6.1 | P |
| | The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by: | | N |
| | $t_{\max} = 10000/E_{\text{UVA}} \text{ s}$ | | N |

| IEC 62471 | | | |
|-----------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 4.3.3 | Retinal blue light hazard exposure limit | | P |
| | To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, $B(\lambda)$, i.e., the blue-light weighted radiance, L_B , shall not exceed the levels defined by: | | P |
| | $\int_{300}^{700} L_{\lambda} \cdot B(\lambda) \cdot \Delta\lambda \leq 10^6 \text{ J}\cdot\text{m}^{-2}\cdot\text{sr}^{-1}$ | | N |
| | $\int_{300}^{700} L_{\lambda} \cdot 100 \cdot \Delta\lambda \leq 100 \text{ W}\cdot\text{m}^{-2}\cdot\text{sr}^{-1}$ | See Table 6.1 | P |
| 4.3.4 | Retinal blue light hazard exposure limit - small source | = 0.0017 | P |
| | Thus the spectral irradiance at the eye E_{λ} , weighted against the blue-light hazard function $B(\lambda)$ shall not exceed the levels defined by: see table 4.2 | | P |
| | $\int_{300}^{700} E_{\lambda} \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \text{ J}\cdot\text{m}^{-2}$ | | P |
| | $\int_{300}^{700} E_{\lambda} \cdot 1 \cdot \Delta\lambda \leq 1 \text{ W}\cdot\text{m}^{-2}$ | | P |
| 4.3.5 | Retinal thermal hazard exposure limit | | P |
| | To protect against retinal thermal injury, the integrated spectral radiance of the light source, L_{λ} , weighted by the burn hazard weighting function $R(\lambda)$ (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by: | | P |
| | $\int_{780}^{1400} L_{\lambda} \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{50000}{\alpha} \text{ W}\cdot\text{m}^{-2}\cdot\text{sr}^{-1}$ | See Table 6.1 | P |
| 4.3.6 | Retinal thermal hazard exposure limit – weak visual stimulus | | P |
| | For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, L_{IR} , as viewed by the eye for exposure times greater than 10 s shall be limited to: | | P |
| | $L_{IR} = \int_{780}^{1400} L_{\lambda} \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{6000}{\alpha} \text{ W}\cdot\text{m}^{-2}\cdot\text{sr}^{-1}$ | See Table 6.1 | P |

| IEC 62471 | | | |
|-----------|---|--|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 4.3.7 | Infrared radiation hazard exposure limits for the eye | | P |
| | The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis),ocular exposure to infrared radiation, EIR,over the wavelength range 780 nm to 3000 nm, for times less than 1000 s, shall not exceed: | | N |
| | $E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 18000 \cdot t^{-0,75} \quad \text{W}\cdot\text{m}^{-2}$ | | N |
| | For times greater than 1000 s the limit becomes: | | P |
| | $E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 100 \quad \text{W}\cdot\text{m}^{-2}$ | See Table 6.1 | P |
| 4.3.8 | Thermal hazard exposure limit for the skin | $E_H = 6.745 \times 10^{-2} \text{W}\cdot\text{m}^{-2}$ | P |
| | Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to: | | P |
| | $E_H \cdot t = \sum_{380}^{3000} \sum_t E_{\lambda}(\lambda, t) \cdot \Delta t \cdot \Delta\lambda \leq 20000 \cdot t^{0,25} \quad \text{J}\cdot\text{m}^{-2}$ | $E_H \cdot t = 6.745 \times 10^{-2} \times 10\text{s} = 0.6745 \text{J}\cdot\text{m}^{-2}$ | P |
| 5 | MEASUREMENT OF LAMPS AND LAMP SYSTEMS | | P |
| 5.1 | Measurement conditions | | P |
| | Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification. | Measured at distance of 200.0mm | P |
| 5.1.1 | Lamp ageing (seasoning) | 30 min. | P |
| | Seasoning of lamps shall be done as stated in the Appropriate EN lamp standard. | | N |
| 5.1.2 | Test environment | 25.2 | P |
| | For specific test conditions, see the appropriate EN lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations. | | P |
| 5.1.3 | Extraneous radiation | | P |
| | Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results. | | P |
| 5.1.4 | Lamp operation | | P |

| IEC 62471 | | | |
|-----------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Operation of the test lamp shall be provided in accordance with: | | P |
| | – the appropriate EN lamp standard, or | | N |
| | – the manufacturer' s recommendation | | P |
| 5.1.5 | Lamp system operation | | N |
| | The power source for operation of the test lamp shall be provided in accordance with: | | N |
| | – the appropriate EN standard, or | | N |
| | – the manufacturer' s recommendation | | N |
| 5.2 | Measurement procedure | | P |
| 5.2.1 | Irradiance measurements | | P |
| | Minimum aperture diameter 7mm. | | P |
| | Maximum aperture diameter 50 mm. | | P |
| | The measurement shall be made in that position of the beam giving the maximum reading. | | P |
| | The measurement instrument is adequate calibrated. | See appendix B | P |
| 5.2.2 | Radiance measurements | | P |
| 5.2.2.1 | Standard method | | P |
| | The measurements made with an optical system. | | P |
| | The instrument shall be calibrated to read in absolute radiant power per unit receiving area and per unit solid angle to acceptance averaged over the field of view of the instrument. | | P |
| 5.2.2.2 | Alternative method | | N |
| | Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements. | | N |
| 5.2.3 | Measurement of source size | | P |
| | The determination of θ , the angle subtended by a source, requires the determination of the 50% emission points of the source. | See Table 6.1 | P |
| 5.2.4 | Pulse width measurement for pulsed sources | | N |
| | The determination of t_p , the nominal pulse duration of a source, requires the determination of the time during which the emission is > 50% of its peak value. | | N |
| 5.3 | Analysis methods | | P |
| 5.3.1 | Weighting curve interpolations | | N |
| | To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired. | | N |
| 5.3.2 | Calculations | | P |

| IEC 62471 | | | |
|-----------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted energy. | | P |
| 5.3.3 | Measurement uncertainty | | P |
| | The quality of all measurement results must be quantified by an analysis of the uncertainty. | | P |
| 6 | LAMP CLASSIFICATION | | P |
| | For the purposes of this standard it was decided that the values shall be reported as follows: | | P |
| | – for lamps intended for general lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lux, but not at a distance less than 200 mm | | N |
| | – for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm | | P |
| 6.1 | Continuous wave lamps | | P |
| 6.1.1 | Exempt Group | | P |
| | In the except group are lamps, which does not pose any photobiological hazard. The requirement is met by any lamp that does not pose: | | P |
| | – an actinic ultraviolet hazard (ES) within 8-hours exposure (30000 s), nor | | P |
| | – a near-UV hazard (EUVA) within 1000 s, (about 16 min), nor | | P |

| IEC 62471 | | | |
|-----------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose: | | N |

FINAL

| IEC 62471 | | | |
|-----------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| Table 4.1 | | Spectral weighting function for assessing ultraviolet hazards for skin and eye | | - |
|---|---|--|---|---|
| Wavelength ¹ λ , nm | UV hazard function $S_{uv}(\lambda)$ | Wavelength λ , nm | UV hazard function $S_{uv}(\lambda)$ | |
| 200 | 0,030 | 313* | 0,006 | |
| 205 | 0,051 | 315 | 0,003 | |
| 210 | 0,075 | 316 | 0,0024 | |
| 215 | 0,095 | 317 | 0,0020 | |
| 220 | 0,120 | 318 | 0,0016 | |
| 225 | 0,150 | 319 | 0,0012 | |
| 230 | 0,190 | 320 | 0,0010 | |
| 235 | 0,240 | 322 | 0,00067 | |
| 240 | 0,300 | 323 | 0,00054 | |
| 245 | 0,360 | 325 | 0,00050 | |
| 250 | 0,430 | 328 | 0,00044 | |
| 254* | 0,500 | 330 | 0,00041 | |
| 255 | 0,520 | 333* | 0,00037 | |
| 260 | 0,650 | 335 | 0,00034 | |
| 265 | 0,810 | 340 | 0,00028 | |
| 270 | 1,000 | 345 | 0,00024 | |
| 275 | 0,960 | 350 | 0,00020 | |
| 280* | 0,880 | 355 | 0,00016 | |
| 285 | 0,770 | 360 | 0,00013 | |
| 290 | 0,640 | 365* | 0,00011 | |
| 295 | 0,540 | 370 | 0,000093 | |
| 297* | 0,460 | 375 | 0,000077 | |
| 300 | 0,300 | 380 | 0,000064 | |
| 303* | 0,120 | 385 | 0,000053 | |
| 305 | 0,060 | 390 | 0,000044 | |
| 308 | 0,026 | 395 | 0,000036 | |
| 310 | 0,015 | 400 | 0,000030 | |

¹ Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation at intermediate wavelengths.
* Emission lines of a mercury discharge spectrum.

| IEC 62471 | | | |
|-----------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| Table 4.2 | Spectral weighting functions for assessing retinal hazards from broadband optical sources | | - |
|------------------|---|-------------------------------------|---|
| Wavelength nm | Blue-light hazard function B() | Burn hazard function R() | |
| 300 | 0,01 | - | |
| 305 | 0,01 | - | |
| 310 | 0,01 | - | |
| 315 | 0,01 | - | |
| 320 | 0,01 | - | |
| 325 | 0,01 | - | |
| 330 | 0,01 | - | |
| 335 | 0,01 | - | |
| 340 | 0,01 | - | |
| 345 | 0,01 | - | |
| 350 | 0,01 | - | |
| 355 | 0,01 | - | |
| 360 | 0,01 | - | |
| 365 | 0,01 | - | |
| 370 | 0,01 | - | |
| 375 | 0,01 | - | |
| 380 | 0,01 | 0,1 | |
| 385 | 0,013 | 0,13 | |
| 390 | 0,025 | 0,25 | |
| 395 | 0,05 | 0,5 | |
| 400 | 0,10 | 1,0 | |
| 405 | 0,20 | 2,0 | |
| 410 | 0,40 | 4,0 | |
| 415 | 0,80 | 8,0 | |
| 420 | 0,90 | 9,0 | |
| 425 | 0,95 | 9,5 | |
| 430 | 0,98 | 9,8 | |
| 435 | 1,00 | 10,0 | |
| 440 | 1,00 | 10,0 | |
| 445 | 0,97 | 9,7 | |
| 450 | 0,94 | 9,4 | |
| 455 | 0,90 | 9,0 | |
| 460 | 0,80 | 8,0 | |
| 465 | 0,70 | 7,0 | |
| 470 | 0,62 | 6,2 | |
| 475 | 0,55 | 5,5 | |
| 480 | 0,45 | 4,5 | |
| 485 | 0,40 | 4,0 | |
| 490 | 0,22 | 2,2 | |
| 495 | 0,16 | 1,6 | |
| 500-600 | $10^{[(450-\lambda)/50]}$ | 1,0 | |
| 600-700 | 0,001 | 1,0 | |
| 700-1050 | 0,013 | $10^{[(700-\lambda)/500]}$ | |
| 1050-1150 | 0,025 | 0,2 | |
| 1150-1200 | 0,05 | $0,2 \cdot 100.02^{(1150-\lambda)}$ | |
| 1200-1400 | 0,10 | 0,02 | |


* 1 Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation at intermediate wavelengths.
* Emission lines of a mercury discharge spectrum.

| IEC 62471 | | | |
|-----------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| Table 5.4 Summary of the ELs for the surface of the skin or cornea (irradiance based values) | | | | | |
|---|--------------------------|---------------------|-----------------------------|----------------------------|--|
| Hazard Name | Relevant equation | Wavelength Range nm | Explosure aperture rad(deg) | Limiting aperture rad(deg) | EL in items of constant irradiance W.m ⁻² |
| Actinic UV skin & eye | $E_S = E \cdot S(\cdot)$ | 200 – 400 | < 30000 | 1,4 (80) | 30/t |
| Eye UV-A | $E_{UVA} = E \cdot$ | 315 – 400 | 1000 >1000 | 1,4 (80) | 10000/t 10 |
| Blue-light small source | $E_B = E \cdot B(\cdot)$ | 300 – 700 | 100 >100 | < 0,011 | 100/t 1,0 |
| Eye IR | $E_{IR} = E \cdot$ | 780 – 3000 | 1000 >1000 | 1,4 (80) | 18000/t ^{0,75} 100 |
| Skin thermal | $E_H = E \cdot$ | 380 – 3000 | < 10 | 2 sr | 20000/t ^{0,75} |

| Table 5.5 Summary of the ELs for the retina (radiance based values) | | | | | |
|--|-----------------------------|---------------------|---|--|--|
| Hazard Name | Relevant equation | Wavelength Range nm | Explosure duration Sec | Field of view radians | EL in terms of constant radiance W.m ⁻² .sr ⁻¹) |
| Blue light | $L_B = L \cdot B(\cdot)$ | 300 – 700 | 0,25 – 10 10-100 100-10000 10000 | 0,011• (t/10) 0,011 0,0011• t 0,1 | 10 ⁶ /t 10 ⁶ /t 10 ⁶ /t 100 |
| Retinal thermal | $L_R = L \cdot R(\cdot)$ | 380 – 1400 | < 0,25 0,25 – 10 | 0,0017 0,011• (t/10) | 50000/(• t ^{0,25}) 50000/(• t ^{0,25}) |
| Retinal thermal (weak visual stimulus) | $L_{IR} = L \cdot R(\cdot)$ | 780 – 1400 | > 10 | 0,011 | 6000/ |

Figure of Spectral distribution



FEM

Appendix A - EUT Photos

The overall view of EUT



Appendix B - Test equipment list

| Equipment Description | Model No | BACL# | Manufacturer | Last Cal | Cal Due |
|--------------------------------------|-----------|--------------|--------------|------------|------------|
| UV-VIS-near IR Spectrophotometer | PMS-2000 | T-08-SF213 | EVERFINE | 2018-09-03 | 2019-09-03 |
| Imaging luminance meter | CX-2K | T-08-SF213-1 | EVERFINE | 2018-09-03 | 2019-09-03 |
| Radiation illuminance meter | RD-2000 | T-08-SF213-2 | EVERFINE | 2018-09-03 | 2019-09-03 |
| Radiation illuminance meter | RD-2000 | T-08-SF213-3 | EVERFINE | 2018-09-03 | 2019-09-03 |
| High Accuracy Array | HAAS-2000 | T-08-SF213-4 | EVERFINE | 2018-09-03 | 2019-09-03 |
| 80mm sample integrating sphere | SMS-300 | T-08-SF213-5 | EVERFINE | 2018-09-03 | 2019-09-03 |
| Hygrothermograph | VC230 | T-08-QA015 | VICTOR | 2019-03-17 | 2020-03-17 |
| Steel tape | 5m×19mm | T-08-SF197 | B&Q | 2016-02-25 | 2021-02-23 |
| High power LED aging dc power supply | B12005 | T-08-SF205 | BACL | 2019-03-26 | 2020-03-26 |
| AC power supply | HPA-1103 | T-08-SF129 | EVERFINE | 2019-07-23 | 2020-07-23 |

End of report